

77 DB Open Diesel Generator Air Cooled Single Cylinder Open Generator

Basic Information

. Place of Origin: China Brand Name: **GET** ISO CE · Certification: Negotiable • Delivery Time: 15-20 workdays

LC, T/T, PayPal, Western Union, Small-Payment Terms:

amount payment, Money Gram



Product Specification

. Rated Frequency: 50hz 60hz

Rated Output(kw): 1.8 2.0/ 2.5 2.8/ 4.8 5.0/ 5.0 5.2/ 6.0 6.2/ 6.3

2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 Max Output (kw):

• Rated Voltage (V): 220V Or As Request

7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 • Rated Currency (A):

28.2/28.6 30.9

Rated Rotation Speed

(r/min):

3000 3600

• Phase No.: Single Phase

Power Factor: Insulation Grade: F Pole Number:

• Excitation Mode: Self-excitation & Constant Voltage (AVR)

· Panel Type: General Panel

Product Description

GET2500E GET3500E GET6500E GET7500E GET8500E GET9500E Open Type Diesel Generator

77 DB Open Type Diesel Generator Single Cylinder Air-Cooled

5						
Rated Output(kw):	1.8 2.0/ 2.5 2.8/ 4.8 5.0/ 5.0 5.2/ 6.0 6.2/ 6.3 6.8					
Rated Voltage (V):	220V Or As Request					
Rated Rotation	3000 3600					
Speed (r/min):						
Power Factor:	1					
Pole Number:	2					
Panel Type:	General Panel					
Connection Pole:	Without					
Overall	690x480x560/ 690x480x560/ 730x495x630/ 730x495x630/					
Dmension(mm):	730x495x630/ 730x495x655					
Working Assorting	66 83 110 115 120 125					
Weight (kg):						
Structure Type:	Open Type					
Cylinder Nobore X	1-73x55/ 1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75					
Stroke (mm):						
Rated Power:	2.5/3000-2.8/3600. 3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000-					
	7.2/3600. 7.6/3000-8.2/3600. 8.1/3000-8.7/3600					
Lubrication System:						
Lube Oil Brand:	CD Grade Or SAE10W-30, 15W-40					
Starting Motor	12V 0.9KW/ 12V 1.2KW					
Capacity:						
Battery Capacity:	12V 20Ah/ 12V 30Ah					
Fuel Tank Capacity	13.5					
(L):						
Rated Frequency:	50hz 60hz					
Max Output (kw):	2.0 2.2/ 2.7 3.0/ 5.2 5.5/ 5.5 5.7/ 6.6 6.8/ 6.9 7.4					
Rated Currency (A):	7.8 8.7/ 11.3 12.7/ 20.5 22.7/ 22.7 23.6/ 27.2 28.2/ 28.6 30.9					
Phase No.:	Single Phase					
Insulation Grade:	F					
Excitation Mode:	Self-excitation & Constant Voltage (AVR)					
Receptacle:	Two Receptacles					
DC 12V Output:	Connection Pole Output					
Dry Weight (kg):	53 70 100 105 110 115					
Noise Level (7m):	77 DB					
Engine Type:	Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled					
Displacement(ml):	247 296 418 456 498 531					
Compression Ratio:						
Fuel Type:	0#(summer)-10#(winter)-35#(chillness) Diesel					
Lube Capacity (L):	0.75 1.1 1.65					
Charging Generator						
Capacity:	12V 8.3A					
Fuel Consumption						
(g/kw*h):	≤280					
(o).						

An open type diesel generator refers to a generator set that is not enclosed within a soundproof housing or enclosure. Instead, it consists of a diesel engine coupled with an alternator to generate electrical power. Open type generators are commonly used in various applications where noise reduction is not a primary concern. Here are some of the features and applications of open type diesel generators:

Features of Open Type Diesel Generators:

Power Output: Open type diesel generators are available in a wide range of power outputs, from small portable units to larger industrial-grade generators. The power output depends on the size and capacity of the generator set.

Durability: Diesel generators are known for their durability and robustness. They are designed to withstand heavy-duty usage and provide a reliable power source in various environments.

Fuel Efficiency: Diesel engines are generally more fuel-efficient compared to gasoline engines. Open type diesel generators can provide long runtimes without frequent refueling, making them suitable for applications where continuous power is required.

Easy Maintenance: Diesel generators are relatively easy to maintain, and their engines are known for their longevity. Routine maintenance tasks include oil and filter changes, fuel filter replacement, and periodic inspections.

Versatility: Open type diesel generators can be used in both stationary and mobile applications. They are commonly used in construction sites, agriculture, mining operations, remote locations, backup power for residential or commercial buildings, and as a primary power source in areas without access to the electrical grid.



DE MAN	DETERME	CETRINE	DETRIORE	CETTURE	DETHIODE	OCTRODE	
MESSAGE Rated Requests (14);7	10 EQ						
MERCH II Relet rotes GP	18 20	23-24	48.50	80 82	63.62	40.48	
Market Str. married (1971)	25 33	27 38	82 88	88 87	68 68	49.74	
MESS States outsign (V)	DOON BEFORE PIER DOON IT IN TERMED						
BESS Select narrano (A)	78.67	113 107	20.5 20.7	20.7 23.6	373 363	280 304	
BERNE Rated totalism operat i citato 1	900 900						
SE Proc VI.	Bill Gright phone						
MARKE Property and Control	1						
MRSS Involvior-Grade	,						
RE NO SERV	*						
Belling botton-note	BERS Bern Set extent 4 contact other both						
BERG New York	# BUT Server Front						
MISSIS NEWSON	MY WHISE BIR TWO HOUSENESS						
Musbell Corredonale	S. Pillout						
MINERC 12Y DOTEY HARM	WIRESE Connection print output						
MAIR C Denal december (Lx W x W) Term (excusion.	69074807560	230'480'030	P9014867608	73074907000	75074007600	
Mill Dry weight (by)	10	70	100	100	110	178	
STATE FOR Victing searching printed by I	- 64	80	710	115	130	105	
Mark Strategy Strategy Street (Tex.)	35	IT	27	77	77	777	
MARK Elevator ton	Gare too						
26 Street Script Corpina Market	detring	GETCWF	GETTMEA	GETTINE	DETHOR	GETHEF	
# British Crypto Type	Drafe sylvates, perticul, haz-stroke, dread transfers, air control						
PLEM-REF BIR Cylinder NOhorse cylinder mm	1.73786	1.79763	1-8679	1-8673	1-8075	1.0075	
### Osphromet (mi.)	247	200	410	168	401	SDR	
BEE 6 4 personners fluted power	25/900 2,8/9800	3.00'0000 A/9000	5.7/2000 5.5/5000	9.5/2000-7.2/2000	T-0-9000 9-2/9000	8.100004.7088	
ERIC Compression-rate	2004	8091	1004	1991	19.97	1001	
WRITE LIDEOUGH WINDS	E. C. VARIOTE Property student						
BRYS Statio sales	R STR BOTH HOLE - CHOIC STAT						
BBBS Nerge	SF(東京)-TSF(東京)-TSF(福華)東南SF(purmer)-SSF(select)-SSF(chileses) deep						
SKRIMEN Line of trees	CD GROW O SANETIRY SEL TRIVING						
選手提手機 Lube sapedy (L.)	0.75	1.1	1.80	1.69	1.85	1.66	
MACRATE Strengwater capacity (VANV)	109 OUNY	TOY COM	107 5,907	TOV COMP	109 1,009	TOV LIME	
NAZARES Charges promise capacity (7-8)	DV 63A						
WENTER Salvey reportly (mile)	129	204A	129 3000		97 868		
MACRES Fool consumption (gharts)	-CHE						
MARKET Ford took corporate (), (9.1						
HARLE THE CONTRACT SERVICE (IN)	- 4	10			1	7.	

GET Wuxi Guangertai Power Machinery Co.,Ltd



NO.88 Shenxing East Road, Wanshi Town, Yixing City, CHINA