



White 9500T Silent Diesel Generator Electric Start Silent Generator

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: GET
- Certification: ISO CE
- Price: Negotiable
- Delivery Time: 15-20 workdays
- Payment Terms: LC, T/T, PayPal, Western Union, Small-amount payment, Money Gram



Product Specification

- Rated Frequency: 50hz 60hz
- Rated Output(kw): 2.5 2.8/ 4.5 4.8/ 4.8 5.0/ 5.7 6.0/ 6.0 6.3
- Max Output (kw): 2.7 3.0/ 5.0 5.2/ 5.2/5.5/ 6.3 6.9/ 6.8 7.7
- Rated Voltage (V): 220V Or As Request
- Rated Current (A): 11.3 12.7/ 20.4 21.8/ 21.8 22.7/ 25.9 27.2/ 27.2 28.6
- Rated Rotation Speed (r/min): 3000 3600
- Phase No.: Single Phase
- Power Factor: 1
- Insulation Grade: F
- Pole Number: 2
- Excitation Mode: Self-excitation & Constant Voltage (AVR)
- Panel Type: General Panel
- Receptacle: Two Receptacles
- Operation Mode: Without

for more products please visit us on dieseleenginepumps.com

GET9500T Silent Diesel Generator White Electric Start Silent Generator

Lower dB ratings indicate quieter operation.

Rated Frequency:	50hz 60hz
Max Output (kw):	2.7 3.0/ 5.0 5.2/ 5.2/5.5/ 6.3 6.9/ 6.8 7.7
Rated Currency (A):	11.3 12.7/ 20.4 21.8/ 21.8 22.7/ 25.9 27.2/ 27.2 28.6
Phase No.:	Single Phase
Insulation Grade:	F
Excitation Mode:	Self-excitation & Constant Voltage (AVR)
Receptacle:	Two Receptacles
DC 12V Output:	Connection Pole Output
Dry Weight (kg):	164 150 150 153 161
Noise Level (7m):	72 DB
Engine Type:	Single Cylinder, Vertical, Four Stroke, Direct Injection, Air-cooled
Displacement(ml):	296 418 456 498 531
Compression Ratio:	20:01, 19:01
Starting System:	Electric Start
Lube Oil Brand:	CD Grade Or SAE10W-30, 15W-40
Starting Motor Capacity:	12V 0.9KW/ 12V 1.2KW
Battery Capacity:	12V 30Ah
Fuel Tank Capacity (L):	15
Rated Output(kw):	2.5 2.8/ 4.5 4.8/ 4.8 5.0/ 5.7 6.0/ 6.0 6.3
Rated Voltage (V):	220V Or As Request
Rated Rotation Speed (r/min):	3000 3600
Power Factor:	1
Pole Number:	2
Panel Type:	General Panel
Connection Pole:	Without
Overall Dmension(mm):	945*555*700
Working Assorting Weight (kg):	179 185 186 186 187
Structure Type:	Silent Type
Cylinder No. -bore X Stroke (mm):	1-78x62/ 1-86x72/ 1-88x75/ 1-92x75/ 1-95x75
Rated Power:	3.68/3000-4/3600. 5.7/3000-6.3/3600. 6.5/3000-7.2/3600. 7.6/3000-8.2/3600. 8.1/3000-8.7/3600
Lubrication System:	Pressure Splashed
Fuel Type:	0#(summer)-10#(winter)-35#(chillness) Diesel
Lube Capacity (L):	1.1/ 1.65
Charging Generator Capacity:	12V 8.3A
Fuel Consumption (g/kw*h):	≤280

[illegible]



Wuxi Guangertai Power Machinery Co.,Ltd



13813650506



2415819289@qq.com



dieselenginepumps.com

NO.88 Shenxing East Road, Wanshi Town, Yixing City, CHINA