



173F 178F Portable Fire Water Pump 4in Small Fire Fighting Pump

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: GET
- Certification: ISO CE
- Price: Negotiable
- Delivery Time: 15-20 workdays
- Payment Terms: LC, T/T, PayPal, Western Union, Small-amount payment, Money Gram



Product Specification

- Type: Portable Diesel Fire Pump
- Suction/discharger Port Diameter Mm(inch): 50(2"). 80(3"). 100(4"). 150(6")
- Discharge Capacity m³/h): 30 40 110 150
- Total Head Lift: 25m 26m 22m 20m
- Self-priming Time (s/4m): 80 120 180 180
- Max Suction Head: 8m 8m 8m 6m
- Rotation Speed (r/min): 3600
- Noise Level Db(A)/7m): 85
- Overall Dimension(mm): 510x455x640. 560x455x655. 650x470x700. 770x574x785
- Dry Weight: 44kg 50kg 71kg 95kg
- Engine Model: GET173F GET178F GET186FA GET192F
- Rated Power: 2.8kw 4kw 6.3kw 8.5kw
- Fuel Consumption G/kw.h: 288 285 281 281
- Displacement (cm³): 247 300 410 400

for more products please visit us on dieselenginepumps.com

Product Description

Portable Fire Water Pump Diesel Engine High Efficiency

Fire pump is a kind of pump equipment specially used for fire extinguishing and fire emergency. It has the following characteristics:

1. High-pressure capability: Fire pumps are capable of providing high-pressure water flow to meet the needs of fire extinguishing operations. They are usually able to generate high water pressure to effectively send water to long distances or high places for the purpose of extinguishing fires.
2. Quick Start: In an emergency, time is of the essence. Fire pumps are usually equipped with a quick start system to ensure that they start up and start working in the shortest possible time. This quickly provides the required water source and pressure to support firefighting operations.
3. Self-priming ability: Fire pumps usually have self-priming capabilities and can automatically pump water from the water source without the need for additional suction pipes or manual water suction. This allows the fire pump to respond quickly to emergencies and quickly introduce water into the system.

Model	JBC6/10
Type	vacuum pump
Max.Flow(T/h)	48
MAX.Lift(m)	60
Rated Speed(rpm)	3600
Water Shot Height	35m
Engine	190F
Maximum Suction Height(m)	7
Self-priming Time(S)	20
Discharge Port Diameter(mm)	65
N.W/G.W(KG)	91/100
Dimensions(mm)	
Loading Qty(20GP/40HQ)	
Model	JBC6/15
Type	vacuum pump
Max.Flow(T/h)	54
MAX.Lift(m)	80
Rated Speed(rpm)	3600
Water Shot Height	35
Engine	192
Maximum Suction Height(m)	7
Self-priming Time(S)	20
Discharge Port Diameter(mm)	65
N.W/G.W(KG)	94/103
Dimensions(mm)	
Loading Qty(20GP/40HQ)	





Wuxi Guangertai Power Machinery Co.,Ltd



13813650506



2415819289@qq.com



dieselenginepumps.com

NO.88 Shenxing East Road, Wanshi Town, Yixing City, CHINA